

Nonprovisional Patent Application

Title: Consistency Determining Method and System

PRIORITY

SERIAL NO: 09/520,915, FILED: MARCH 8, 2000
SERIAL NO.: 60/190,743, FILED: MARCH 20, 2001
SERIAL NO.: 60/196,279, FILED: APRIL 9, 2000

Inventor: Ola M. Johansson
2190 WIPPLETREE LANE
BROOKFIELD, WI 53005
USA
A CITIZEN OF SWEDEN

Assignee:

J & L FIBER SYSTEMS, INC.
809 Philip Drive
Waukesha, WI 53186
USA

CERTIFICATION UNDER 37 C.F.R. § 1.10

Express Mail Label No. EL647007419US

Date of Deposit: March 20, 2001

I hereby certify that this correspondence is being deposited with the U.S. Postal Service in "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to the Director of the U.S. Patent & Trademark Office, Box Patent Application, Washington, D.C. 20231-9999.



Signature

CONSISTENCY DETERMINING METHOD AND SYSTEM

Cross-Reference To Related Applications

This application is a continuation-in-part of presently copending U.S. Patent
5 Application Serial No. 09/520,915 that was filed in the U.S. Patent Office on March 8,
2000. This application also claims priority under 35 U.S.C. §119(e) to U.S. Provisional
Patent Application No. 60/190,743, filed March 20, 2000, and U.S. Provisional Patent
Application No. 60/196,279, filed April 9, 2000, the entirety of both which are
incorporated by reference herein.

10

Field of the Invention

The present invention relates to a method and system for determining consistency
of stock being refined by a disk refiner as well as a method and system for controlling
refiner operation based on consistency.

Background of the Invention

15

Many products we use every day are made from fibers. Examples of just a few of
these products include paper, personal hygiene products, diapers, plates, containers, and
packaging. Making products from wood fibers, cloth fibers and the like, involves
breaking solid matter into fibrous matter. This also involves processing the fibrous matter
into individual fibers that become fibrillated or frayed so they more tightly mesh with
20 each other to form a finished fiber product that is desirably strong, tough, and resilient.

In fiber product manufacturing, refiners are devices used to process the fibrous
matter, such as wood chips, pulp, fabric, and the like, into fibers and to further fibrillate

existing fibers. The fibrous matter is transported in a liquid stock slurry to each refiner using a feed screw driven by a motor. Each refiner has at least one pair of circular ridged refiner discs that face each other. During refining, fibrous matter in the stock to be refined is introduced into a gap between the discs that usually is quite small. Relative rotation
5 between the discs during operation causes the fibrous matter to be fibrillated as the stock passes radially outwardly between the discs.

One example of a refiner that is a disc refiner is shown and disclosed in U.S. Patent No. 5,425,508. However, many different kinds of refiners are in use today. For example, there are counterrotating refiners, double disc or twin refiners, and conical disc
10 refiners. Conical disc refiners are often referred to in the industry as CD refiners.

Each refiner has at least one motor coupled to a rotor carrying at least one of the refiner discs. During operation, the load on this motor can vary greatly over time depending on many parameters. For example, as the mass flow rate of the stock slurry being introduced into a refiner increases, the load on the motor increases. It is also known
15 that the load on the motor will decrease as the flow rate of dilution water is increased.

During refiner operation, a great deal of heat is produced in the refining zone between each pair of opposed refiner discs. The refining zone typically gets so hot that steam is produced, which significantly reduces the amount of liquid in the refining zone. This reduction of liquid in the refining zone leads to increased friction between opposed
20 refiner discs, which increases the load on the motor of the refiner. When it becomes necessary to decrease this friction, water is added to the refiner. The water that is added is typically referred to as dilution water.

One problem that has yet to be adequately solved is how to control refiner operation so that the finished fiber product has certain desired characteristics that do not vary greatly over time. For example, paper producers have found it very difficult to consistently control refiner operation from one hour to the next so that a batch of paper produced has consistent quality. As a result, it is not unusual for some paper produced to be scrapped and reprocessed or sold cheaply as job lot. Either way, these variations in quality are undesirable and costly.

Another related problem is how to control refiner operation to repeatedly obtain certain desired finished fiber product characteristics in different batches run at different times, such as different batches run on different days. This problem is not trivial as it is very desirable for paper producers be able to produce different batches of paper having nearly the same characteristics, such as tear strength, tensile strength, brightness, opacity and the like.

In the past, control systems and methods have been employed that attempt to automatically control refiner operation to solve at least some of these problems. One common control system used in paper mills and fiber processing plants throughout the world is a Distributed Control System (DCS). A DCS communicates with each refiner in the mill or fiber processing plant and often communicates with other fiber product processing equipment. A DCS monitors operation of each refiner in a particular fiber product processing plant by monitoring refiner parameters that typically include the main motor power, the dilution water flow rate, the hydraulic load, the feed screw speed, the refiner case pressure, the inlet pressure, and the refiner gap. In addition to monitoring

refiner operation, the DCS also automatically controls refiner operation by attempting to hold the load of the motor of each refiner at a particular setpoint. In fact, many refiners have their own motor load setpoint. When the motor load of a particular refiner rises above its setpoint, the DCS adds more dilution water to the refiner to decrease friction.

- 5 When the motor load decreases below the setpoint, dilution water is reduced or stopped.

During refiner operation, pulp quality and the load on the refiner motor vary, sometimes quite dramatically, over time. Although the aforementioned DCS control method attempts to account for these variations and prevent the aforementioned problems from occurring, its control method assumes that the mass flow of fibrous matter in the

10 stock entering the refiner is constant because the speed of the feed screw supplying the stock is constant. Unfortunately, as a result, there are times when controlling the dilution water flow rate does not decrease or increase motor load in the desired manner. This disparity leads to changes in refining intensity and pulp quality because the specific energy inputted into refining the fibrous matter is not constant. These changes are

15 undesirable because they ultimately lead to the aforementioned problems, as well as other problems.

In the past, consistency has been measured externally of a refiner in an effort to determine how well the refiner is operating. After evaluating the consistency measurement, there are times where an operator will manually make an adjustment to the

20 refiner in an effort to try to get the consistency closer to a desired value or range. Unfortunately, it takes a long time, often several hours or longer, before the operator will know whether his or her adjustment had the desired impact on consistency. This hit and

miss approach is inexact and inefficient.

This delay is believed to be caused by at least two problems, if not more. First, it takes a long time, often several hours or possibly even days, for the refiner to reach steady state operation before an operator will know what kind of effect that the change had.

5 Second, consistency measurements are taken outside the refiner using equipment and methods that are slow, which also delays how fast an operator can obtain feedback. In any event, because the present methods and devices for measuring consistency are slow and there is a corresponding delay in recognizing that the refiner is operating in a steady state condition, the operator is forced to wait a long time until they know with some
10 certainty what kind of effect their change had. This means, that the refiner can operate inefficiently for hours, if not days, before the operator, using this trial and error method, finally settles on a combination of operating settings that are more to his or her liking.

Hence, while some refiner process control methods have proven beneficial in the past, they in no way have resulted in the type of control over finished fiber product
15 parameters and the repeatability of these parameters that is desired. Thus, additional improvements in refiner process control and consistency measurement are needed.

Summary of the Invention

A system for and method of determining stock consistency. The invention includes one or more sensors that sense temperature and/or pressure of stock adjacent or
20 in the refining zone during refiner operation. In one preferred embodiment, one or more sensors in the refining zone provide real time temperature and/or pressure data from which a consistency is determined. A plurality of sensors can be used. Sensors can be

distributed radially along the refining zone to provide a distribution of temperature and/or pressure data from which a consistency is determined. Using the system and method of the invention, consistency can be quickly measured in no more than five minutes and preferably is measured in real time. In one preferred embodiment and method,

5 consistency is measured a plurality of times a second and preferably at a rate of about twenty times a second.

The consistency can then be used to control or help control refiner operation. For example, in one preferred embodiment, the dilution water to the refiner is regulated based on stock consistency. In another preferred method, the volumetric flow rate of the stock is

10 regulated based on stock consistency. If desired, regulation of volumetric flow rate and dilution water can both be based on stock consistency. If desired, another parameter, such as refiner gap, can be regulated based on consistency.

Where refiner temperature is used in determining consistency, the refiner temperature is a temperature of stock inside the refiner or adjacent its inlet or outlet. In

15 one preferred implementation, the refiner temperature is a temperature of stock in the refining zone. Where there is more than one sensor in the refining zone, the temperature can be provided by a particular selected sensor or calculated based on the sensor data from more than one sensor. In one preferred embodiment, temperature measurements from multiple sensors are averaged. In another embodiment, a temperature profile using

20 data from each sensor is used.

Where refiner pressure is used in determining consistency, the pressure preferably is a pressure inside the refiner, such as a pressure in the refining zone, or a pressure inside

the refiner adjacent an inlet or outlet. Where there is more than one sensor in the refining zone, the pressure can be provided by a particular selected sensor or calculated based on the sensor data from more than one sensor. In one preferred embodiment, pressure measurements from multiple sensors are averaged. In another embodiment, a pressure
5 profile using data from each sensor is used.

In one preferred implementation of the method of determining consistency, the method uses temperature or pressure measured inside the refining zone along with other refiner parameters in determining the consistency of stock in the refining zone as a function of time and location in the refining zone. This method advantageously permits
10 consistency of stock to be determined in real time in the refining zone.

Where volumetric stock flow or mass flow is regulated, it preferably is regulated by controlling the speed of a feed screw that provides the refiner with stock or fiber for stock. Where dilution water flow is regulated, it preferably is regulated by controlling operation of the dilution pump. Other refiner parameters can be controlling using the
15 method of this invention.

So that the process can be controlled despite changes in refiner operation not due to regulation using the method, one preferred implementation pauses to permit refiner operation to stabilize before resuming regulation of refiner operation. For example, where an operator manually changes refiner operation, regulation is paused preferably
20 until refiner operation stabilizes. The same is true where a refiner is also subject to control of a processing device, such as a Distributed Control System (DCS).

In one preferred embodiment, the method is implemented in the form of a

controller that preferably is a PI or a PID controller. If desired, a proportional controller can be used. The controller can be a digital or analog controller and can be configured to operate with a processor such as the digital processor of a personal computer, a DCS, a programmable controller or the like.

5 The system includes a processor that receives data related to refiner operation. Suitable data includes data related to the process variable or variables used in regulating refiner operation. In one preferred embodiment, the processor receives data related to one or more of the following parameters: the power inputted into the refiner, the feed screw speed (or volumetric stock flow or feed rate), the temperature of the stock before it enters
10 the refiner, the temperature of stock after it leaves the refiner, a refiner temperature, a refiner pressure, the force exerted on the refiner disks urging them together, the dilution motor power of the dilution pump, the chip washing water temperature, the dilution water temperature, the gap between the refiner disks, as well as other parameters. At least three of these parameters are used in determining consistency.

15 In carrying out a method of refiner control using consistency, the processor outputs at least one control signal. Each control signal can be directly provided to the refiner or a component related to the refiner, such as the feed screw or dilution water pump. If desired, each control signal can be provided to another processor, such as a DCS, that causes the DCS to regulate the desired parameter. For example, a control signal
20 can be provided to the DCS that causes the DCS to change feed screw speed. Another control signal can be provided to the DCS that causes the dilution water flow rate to change. Another control signal can be provided to the DCS that causes the refiner gap to

change.

Using a method and system of this invention, control changes can be made to the refiner at a rate of at least one every five minutes and preferably faster. For example, in one preferred embodiment, real time control of the refiner is achieved. Preferably, the system and method enables a plurality of the aforementioned setting changes to be made
 5 per second and as fast as at a rate of about twenty hertz.

In one preferred embodiment, each sensor is carried by a refiner disk or segment of the disk. In one preferred sensor disk or sensor disk segment, each sensor is imbedded in the refining surface of the disk or segment.

10 In a preferred sensor embodiment, the sensor has a sensing element carried by a spacer that spaces the sensing element from the material of the disk or segment in which it is imbedded. This prevents the sensor from detecting the temperature of the disc or disc segment, and, instead, when insulated, the sensor detects the temperature of the stock. One preferred spacer is made from an insulating material that preferably thermally
 15 insulates the sensing element from the thermal mass of the refiner disk material.

Other objects, features, and advantages of the present invention include one or more of the following: a method and system for determining consistency at or close to the refining zone; a method and system for determining consistency in real time in the refining zone; a method and system for determining consistency in the refining zone as a
 20 function of position in the refining zone; a method and system for using determined consistency in controlling some aspect of refiner operation; a method and system that controls refiner operation in real time based on consistency measured in real time; and a

method and system for controlling refiner operation based on consistency that accommodates changes to other refiner settings; is a method and system for measuring consistency that is reliable, economical, easy to manufacture and install, repeatable, fast, rugged, and efficient; and is a method and system for controlling refiner operation based
5 on consistency that is also reliable, economical, fast, rugged, and efficient.

Other objects, features, and advantages of the present invention will become apparent to those skilled in the art from the detailed description and the accompanying drawings. It should be understood, however, that the detailed description and accompanying drawings, while indicating at least one preferred embodiment of the
10 present invention, are given by way of illustration and not of limitation. Many changes and modifications may be made within the scope of the present invention without departing from the spirit thereof, and the invention includes all such modifications.

Brief Description of the Drawings

Preferred exemplary embodiments of the invention are illustrated in the
15 accompanying drawings in which like reference numerals represent like parts throughout and in which:

FIG. 1 is a schematic view of a first embodiment of a refiner monitoring and control system;

FIG. 2 is a schematic view of a second embodiment of a refiner monitoring and
20 control system;

FIG. 3 is front plan view of a cabinet housing a control computer of the refiner monitoring and control system;

FIG. 4 is a fragmentary cross sectional view of an exemplary twin refiner;

FIG. 5 is a schematic of a system for supplying the refiner with stock;

FIG. 6 is a front plan view of an exemplary refiner disk segment;

FIG. 7 is a front plan view of a refiner disk segment that has a plate with sensors

5 used to sense a parameter, such as a process variable, in the refining zone;

FIG. 8 is an exploded side view of a second refiner disk with sensors embedded in the refining surface of the disk;

FIG. 9 is a graph showing a generally linear relationship between a process variable, namely refiner temperature, and the controlled variable, namely feed screw
10 speed;

FIG. 10 is a graph depicting controlling the process variable, namely refiner temperature, by regulating the controlled variable, namely volumetric flow rate of stock entering the refiner;

FIG. 11 is a graph illustrating the relationship between a process variable, namely
15 refiner temperature, and a controlled variable, namely dilution water flow rate;

FIG. 12 is a flowchart illustrating a preferred method of controlling refiner operation;

FIG. 13 is a graph depicting a tolerance or band around a process variable setpoint used in controlling refiner operation;

20 FIG. 14 depicts one preferred implementation of the control method;

FIG. 15 is a graph illustrating a method of changing a process variable setpoint in response to a change in refiner operation;

FIG. 16 is a schematic of a method of changing the setpoint in response to a change in refiner operation;

FIG. 17 is a schematic depicting a second preferred implementation of the control method;

5 FIG. 18 is a schematic depicting a preferred implementation of the control method using two control loops that have two process variables that can be different;

FIG. 19 is a schematic depicting a second preferred implementation of the control method using two control loops;

10 FIG. 20 is a control block diagram depicting one preferred implementation of the control method;

FIG. 21 is a control block diagram depicting a second preferred implementation of the control method having two control loops;

15 FIG. 22 is a graph illustrating a change in a refiner operating parameter putting a controller of the control method on hold and then releasing the controller when a process variable of the control method has stabilized;

FIG. 23 depicts a piece of fiber being refined by a pair of refiner plates and the strain imparted on the fiber by the plates;

FIG. 24 is a load-deflection or stress-strain curve for wood being refined;

20 FIG. 25 illustrates a typical temperature profile in the refining zone of a single disc high consistency refiner;

FIG. 26 is a plot of refining zone temperature as a function of radius;

FIG. 27 is a schematic of a system for measuring consistency and for controlling

refiner operation using the measured consistency;

FIG. 28 is a graph illustrating operation of a controller that controls refiner operation based on measured consistency;

FIG. 29 is a graph depicting refiner performance with and without refiner control
 5 based on consistency; and

FIG. 30 illustrates operation of a refiner being controlled by a controller that controls refiner operation based on measured consistency.

Detailed Description of Preferred Embodiments

FIG. 1 schematically illustrates a system 30 for determining consistency of stock
 10 being refined and can be used to determine consistency in one or more disc refiners 32a, 32b, or 32c. The system includes a processor 34 that accepts data from sensors from which consistency is determined and performs calculations to determine consistency. In one preferred embodiment, the processor 34 can also control some aspect of operation of a refiner. For example, the processor 34 can also control operation of a feed screw 66,
 15 which is shown in FIG. 5, and which is discussed below, that supplies the refiner with stock. The feed screw 66 is not part of the refiner itself and, instead, is a separate part that feeds stock to the refiner. In another preferred embodiment, the processor 34 can also control the flow rate of dilution water to the refiner. The mass flow can be regulated to help keep a process variable at or desirably close to a consistency setpoint that can change
 20 during operation. When some aspect of refiner operation is changed, the control processor 34 stops regulation for a period of time to allow the change to take effect and cause a new

setpoint to be reached. The control processor 34 then resumes regulating mass flow using the new setpoint.

In a preferred embodiment of the system 30, the processor 34 comprises a computer 38 that can include a display 40, and one or more input/output devices 42, such as a keyboard and/or a mouse. Such a computer 38 can be a personal computer, a mainframe computer, a programmable controller, or another type of processing device. If desired, the computer 38 can have on-board memory and can have an on-board storage device.

In the preferred embodiment shown in FIG. 1, the processor 34 preferably also has or includes an input/output device 44 that comprises at least one data acquisition device or a data acquisition system capable of receiving data from one or more of the refiners 32a, 32b, and 32c. For example, in the embodiment of FIG. 1, at least three refiners 32a, 32b, and 32c are linked to the processor 34. This device 44 can be a separate component linking the processor 34 and the refiners 32a, 32b, and 32c in the manner depicted in FIG. 1, or can be an integral part of the processor 34.

The processor 34 and input/output device 44 can be housed in a cabinet 82 (FIG. 3) that can be located in a fiber processing plant, such as a paper mill or the like. The display 40 can be remotely located, such as in a control room of the fiber processing plant. If desired, the processor 34 can be a Distributed Control System (DCS) at the fiber processing plant or can be a component of the DCS.

The processor 34 can communicate via a link 46 with an off-site computer 48 that is used for troubleshooting and downloading updates or changes to the method of refiner

control carried out by the processor 34. Such a link 46 can be a wireless link or a wire link between computers 38 and 48. Examples of suitable links 46 include a link via the Internet, such as an FTP or TCP/IP link, or a direct telephone link.

The processor 34 is directly or indirectly connected by links, indicated by
 5 reference numerals 50-60 in FIG. 1, to each one of the refiners 32a, 32b and 32c. For example, one or more of the links 50-60 can comprise a cable or a wireless communication link or the like.

The processor 34 is shown in FIG. 1 as being connected by a link 62 to the input/output device 44. In one preferred embodiment, the device 44 is a data acquisition
 10 and control system that includes ports or modules 64. Where data acquisition is needed, each port or module can comprise a data acquisition card. If desired, the device 44 can be comprised of one or more data acquisition cards installed in slots inside computer 38. While FIG. 1 depicts a link from each one of the refiners 32a, 32b, and 32c running to a single card or module, a dedicated card or module can accept two or more such links.

15 Each refiner 32a, 32b, and 32c has a plurality of sensors that provide data to the processor 34. For example, data from at least one sensor 70 relating to temperature, pressure or a combination of temperature and pressure are communicated via link 50 to processor 34. Data from other sensors 72-80 are also directly or indirectly utilized in
 20 determining consistency. For example, sensors 72-80 provide data relating to one or more of the following parameters: refiner main motor power, refiner plate force, the refiner gap, the rate of flow of dilution water added during refining, conveyor screw rotation, the flow rate of fibrous matter being introduced into the refiner, such as fiber mass flow rate

and stock flow rate, and/or rotational speed, as well as consistency. Where the processor 34 is a DCS, all of this sensor data is obtained during refiner operation by the DCS.

Where refiner main motor power is monitored, an example of a suitable sensor is one that senses the voltage or current from a current transformer coupled to the refiner motor. Where refiner plate force is monitored, examples of suitable sensors include one or more of the following: an accelerometer, a strain gauge, or a pressure sensor that senses the pressure or force urging the refiner plates toward each other. Where refiner gap is monitored, examples of sensors include one or more of the following: an inductive sensor carried by at least one of the refiner plates or a Hall effect sensor. Where conveyor screw rotation is monitored, a sensor on the conveyor screw motor can be used to provide, for example, the rate of screw rotation. Where rate of flow of dilution water is monitored, a flowmeter can be used. A flowmeter is an example of a sensor that can be used to provide data from which a flow rate of fibrous matter into the refiner can be obtained. Where a flow meter is used, examples of suitable flow meters that can be used include paddle-wheel type sensors, optical sensors, viscosity meters, or other types of flow meters. Sensor data from one or more sensors, including the aforementioned sensors, can be used in making a consistency measurement that can be used as a setpoint by the processor 34.

A number of these refiner-related sensors and other sensors that can be monitored by the system 30 of this invention are disclosed in more detail in one or more of U.S. Patent Nos. 4,148,439; 4,184,204; 4,626,318; 4,661,911; 4,820,980; 5,011,090; 5,016,824; 5,491,340; and 5,605,290, the disclosures of each of which are expressly

incorporated herein by reference.

FIG. 2 schematically illustrates another preferred embodiment of system 30'. The processor 34 is a computer 38 that is located in a cabinet 82 that is located on site. There is a link 84 from the processor 34 to a signal conditioner 86 carried by the refiner 32. The
5 signal conditioner 86 is attached by another link 88 to each sensor 70.

The signal conditioner 86 connects with each sensor 70 and converts the sensor output to an electrical signal that is transmitted to the processor 34. For example, one preferred signal conditioner 86 typically outputs a current (for each sensor) in the range of between four and twenty milliamperes. The magnitude of the signal depends upon the
10 input to the sensor (and other factors including the type of sensor or sensors) and provides the processor the information from which it can determine a sensor measurement. If desired, more than one signal conditioner can be mounted to the casing or housing of the refiner 32. As is depicted in FIG. 2, the signal from each sensor 70 can first be communicated by a link 84 to a DCS 94 before being communicated to processor 34. In
15 some instances, a signal conditioner 86 may not be needed.

For sending information, the processor 34 is connected by a communications link 100, such as a phone line, to a device 102 located in a control room that preferably is located in the fiber processing plant. The device 102 can be a computer that includes a display 104 upon which graphical information is shown that relates to refiner operation
20 and can relate to control.

The processor 34 is depicted in FIG. 2 as being connected by another communications link 92 to a DCS 94 that preferably is located on site. The DCS 94 is

connected by a second link 96 to one or more of refiner sensors 72, 74, 76, 78 and 80 that provide the DCS with information about a number of parameters that relate to refiner operation. A third link 98 connects the DCS to each feed screw motor (or feed screw motor controller) 66 and each dilution water motor (or feed screw motor controller) 68, only one of which is schematically depicted in FIG. 2. The link 98 can include a separate link to each feed screw motor (or motor controller) 66 and each dilution water motor (or motor controller) 68 for that particular refiner 32. At least one of the purposes of link 98 is to convey control signals from the DCS to each feed screw motor (or motor controller) 66 and each dilution water motor (or motor controller) 68 to control their operation.

Another purpose of link 98 can be to provide feedback about motor speed so that the mass flow rate of the feed screw and flow rate of dilution water can be determined.

The link 92 provides the processor 34 with information from the DCS 94 that preferably includes the main motor power of the refiner 32, the force exerted on the refiner disks urging them together (or hydraulic pressure or force), the dilution motor power of the refiner for each dilution pump, DCS ready status, several other DCS signals, the refiner case pressure, the refiner inlet pressure, the chip washing water temperature, the dilution water temperature, as well as the gap between refiner disks. The link 92 also enables the processor 34 to communicate with the DCS 94 to cause the DCS 94 to change the mass flow rate of stock entering the refiner 32. The link 92 can also be used by the processor 34 to communicate with the DCS 94 to change the rate of flow of dilution water entering the refiner 32. The link 92 preferably comprises a bidirectional communications link. Communication preferably is in the form of a digital or analog

control signal sent by the processor 34 to the DCS 94.

FIG. 3 depicts the contents of a cabinet 82 that houses the processor 34. In addition to any needed data acquisition modules or system (not shown in FIG. 3), the processor 34 can communicate via a link 106 with a connector box 108 that includes a plurality of calibration modules 110. Each calibration module 110 holds calibration data for a particular sensor or a particular set of sensors 70. Each calibration module 110 has on board storage or memory, such as an EPROM, EEPROM, or the like, that holds sensor calibration data. When data is read from a particular sensor or a particular set of sensors 70, the calibration data that relates to that particular sensor or that particular group of sensors 70 is applied to make the resultant sensor measurement more accurate.

The refiner 32 can be a refiner of the type used in thermomechanical pulping, refiner-mechanical pulping, chemithermomechanical pulping, or another type of pulping or fiber processing application where a rotary disk refiner is used. The refiner 32 can be a counterrotating refiner, a double disc or twin refiner, or a conical disc refiner known in the industry as a CD refiner.

An example of a refiner 32 that is a double disc or twin refiner is shown in FIG. 4. The refiner 32 has a housing or casing 90 and an auger 112 mounted therein which urges a stock slurry of liquid and fiber introduced through a stock inlet 114 into the refiner 32. The auger 112 is carried by a shaft 116 that rotates during refiner operation to help supply stock to an arrangement of treating structure 118 within the housing 90. An annular flinger nut 122 is generally in line with the auger 112 and directs the stock radially outwardly to a plurality of opposed sets of breaker bar segments 124 and 126.

Each set of breaker bar segments 124 and 126 preferably is in the form of sectors of an annulus, which together form an encircling section of breaker bars. One set of breaker bar segments 124 is carried by a rotor 120. The other set of breaker bar segments 126 is carried by another portion of the refiner 32, such as a stationary mounting surface 128, *e.g.*, a stator, of the refiner or another rotor (not shown). The stationary mounting surface 128 can comprise a stationary part 130 of the refiner frame, such as the plate shown in FIG. 4.

Stock flows radially outwardly from the breaker bar segments 124 and 126 to a radially outwardly positioned set of opposed refiner discs 132 and 134. This set of refiner discs 132 and 134 preferably is removably mounted to a mounting surface. For example, disc 132 is mounted to the rotor 120 and discs 134 are mounted to mounting surface 128.

The refiner 32 preferably includes a second set of refiner discs 136 and 138 positioned radially outwardly of the first set of discs 132 and 134. The refiner discs 136 and 138 preferably are also removably mounted. For example, disc 136 is mounted to the rotor 120, and disc 138 is mounted to a mounting surface 140. Each pair of discs of each set are spaced apart so as to define a small gap between them that typically is between about 0.005 inches (0.127 mm) and about 0.125 inches (3.175 mm). Each disc can be of unitary construction or can be comprised of a plurality of segments.

The first set of refiner discs 132 and 134 is disposed generally parallel to a radially extending plane 142 that typically is generally perpendicular to an axis 144 of rotation of the auger 112. The second set of refiner discs 136 and 138 can also be disposed generally parallel to this same plane 142. This plane 142 passes through the

refiner gap and refining zone between each pair of opposed refiner disks. Depending on the configuration and type of refiner, different sets of refiner discs can be disposed in different planes.

During operation, the rotor 120 and refiner discs 132 and 136 rotate about axis 144 causing relative rotation between refiner discs 132 and 136 and refiner discs 134 and 138. Typically, each rotor 120 is rotated at a speed of between about 400 and about 3,000 revolutions per minute. During operation, fiber in the stock slurry is refined as it passes between the discs 132, 134, 136, and 138.

FIG. 5 schematically depicts the refiner 32 and includes a fiber delivery system 146 for delivering fibrous matter or fiber to be refined 150 to each inlet 114a and 114b of the refiner 32. The fibrous matter or fiber 148 can be in the form of wood chips, pulp, fabric, or another fiber used in the manufacturing of products made from, at least in part, fiber. The fiber 148 preferably is carried by or entrained in a liquid to form a stock slurry.

In the exemplary preferred embodiment shown in FIG. 3, the fiber 148 is transported along a fiber transport conveyor 150 that urges fiber (preferably in a stock slurry) along its length until it reaches an outlet that can be connected directly or indirectly to a refiner. In the embodiment shown in FIG. 3, the fiber transport conveyor 150 has outlets 152 and 154 that are each connected to a metering conveyor 156 and 158. Each metering conveyor, in turn, is connected to one of the refiner inlets 114a and 114b. This arrangement advantageously enables mass flow to be separately and more precisely metered to each refiner inlet 114a and 114b of a double disc refiner or the like. This arrangement can also be used to distribute and meter fiber 148 to two, three, four, or more

refiners using a common conveyor 150 and a separate metering conveyor for each refiner.

In one preferred embodiment, the fiber transport conveyor 150 includes an auger or screw 160 driven by a motor 162 that can be, for example, an electric motor or a hydraulic motor. The motor 162 can be controlled by the DCS 94 or directly controlled by control processor 34, if desired, in regulating mass flow. Where a metering conveyor is used, each metering conveyor 156 and 158 preferably includes an auger or screw 164 driven by a motor 166. Each motor 166 of each metering conveyor 156 and 158 is controlled by the DCS 94 or by processor 34.

As is shown in FIG. 3, trees 168 typically are processed into chips 148 that are transported by conveyor 150 to an outlet 152 or 154. Chips 148 pass from one of the outlets to one of the metering conveyors 156 or 158. The metering rate of each metering conveyor 156 and 158 is controlled by processor 34 to regulate the mass flow rate of stock entering each refiner inlet 114a and 114b. After being refined by the refiner 32, the refined fiber 170 can be transported to another refiner for further refining, a screen or other filter, or to the fiber processing machine, such as a paper machine, that processes the refined fiber 140 into a product.

FIG. 6 depicts an exemplary segment 172 of a refiner disk that preferably is removable so it can be replaced, such as when it becomes worn. The segment 172 has a plurality of pairs of spaced apart upraised bars 174 that define grooves or channels 176 therebetween. The pattern of bars 174 and grooves 176 shown in FIG. 6 is an exemplary pattern as any pattern of bars 174 and grooves 176 can be used. If desired, surface or subsurface dams 178 can be disposed in one or more of the grooves 176.

During refining, fiber in the stock that is introduced between opposed refiner disks is refined by being ground, abraded, or mashed between opposed bars 174 of the disks. Stock disposed in the grooves 176 and elsewhere between the disks flows radially outwardly and can be urged in an axial direction by dams 178 to further encourage refining of the fiber. Depending on the construction, arrangement and pattern of bars 174 and grooves 176, differences in the angle between the bars 174 of opposed disks due to relative movement between the disks can repeatedly occur. Where and when such differences in angle occur, radial outward flow of stock between the opposed disks is accelerated or pumped. Where and when the bars 174 and grooves 176 of the opposed disks are generally aligned, flow is retarded or held back.

Referring to FIG. 7, a portion of one refiner disk or a refiner disk segment 173 of refiner 32 contains a sensor device 70. The sensor device 70 includes at least one sensor capable of sensing at least one parameter in a refining zone during refiner operation. The sensed parameter can be used as the setpoint or can be used in its determination. In the embodiment shown in FIG. 7, the sensor device 70 is comprised of a sensor assembly 196 that has a plurality of spaced apart sensors 180, 182, 184, 186, 188, 190, 192, and 194. If desired, the sensor assembly 196 can have at least three sensors, at least four sensors, at least five sensors and can have more than eight sensors. Preferably, at least one refiner disk of each refiner 32 being monitored by processor 34 is equipped with a sensor device 70 and, where the refiner disc is segmented, the disc is equipped with at least one sensor segment 173.

In the sensor disk segment embodiment shown in FIG. 7, the sensors 180, 182,

184, 186, 188, 190, 192, and 194 are carried by a bar 198 received in a radial channel or pocket in the face of the segment. The bar 198 can be, for example, frictionally retained, affixed by an adhesive, welded, or retained in the disk or disk segment using fasteners. Each sensor 180, 182, 184, 186, 188, 190, 192, and 194 has at least one wire (not shown) to enable a signal to be communicated from the sensor to the signal conditioner and/or a data acquisition device. Where the segment 173 is carried by a rotor 120, a slip ring (not shown) can be connected to the wires connected to the sensors 180, 182, 184, 186, 188, 190, 192, and 194. Telemetry can also be used.

In another preferred embodiment, FIG. 8 illustrates a different sensing assembly 200 that includes a manifold-like fixture 202 that can have a plurality of outwardly extending and tubular sensor holders 204. In a preferred embodiment, there are no sensor holders as at least part of each sensor 180, 182, 184, 186, 188, 190, 192, and 194 is received in a bore 205 (shown in FIG. 8 in phantom) in the fixture 202. The fixture 202 is disposed in a pocket 208 (shown in phantom in FIG. 8) in the rear of the sensor refiner disk segment 173.

When the disk segment 173 is assembled, each sensor 180, 182, 184, 186, 188, 190, 192, and 194 is received in its own separate bore 210, 212, 214, 216, 218, 220, 222, and 224 such that an axial end of each sensor is exposed to the refining zone during refiner operation. Each sensor 180, 182, 184, 186, 188, 190, 192, and 194 is at least partially received in a spacer 206 that spaces the sensor from the surrounding refiner disk material. At least where the sensor is a temperature sensor, the spacer 206 is an insulator that thermally insulates the sensor from the thermal mass of the refiner disk segment 173.

A preferred insulating spacer 206 is made of ceramic, such as alumina or mullite.

When assembled to the segment 173, an axial end of each sensor 180, 182, 184, 186, 188, 190, 192, and 194 is disposed no higher than the axial surface 175 of the bars 174 of the disk segment 173. Preferably, the axial end of each sensor 180, 182, 184, 186, 188, 190, 192, and 194 is disposed at least about fifty thousandths of an inch below the axial surface 175 of the portion of the bar 174 adjacent the sensor. In one preferred embodiment, each sensor 180, 182, 184, 186, 188, 190, 192, and 194 is disposed at least one-hundred thousandths of an inch below the axial surface of the portion of the bar 174 adjacent the sensor.

When assembled, each sensor is telescopically received in one of the spacers 206, and the spacer 206 is at least partially telescopically received in one of the bores 205 in the fixture 202. Each sensor has at least one wire 226 that passes through one of the insulating tubes 206, one of the sensor holders 204, and through a hollow in the bar 202 until it reaches outlet 228 located adjacent one end of the bar 202. Although not shown, a sealant, such as silicone or a high temperature refiner plate potting compound, can be disposed in a hollow 227 in the fixture 202 to protect the wires 226 and prevent steam and stock from leaking from the refining zone. In another preferred embodiment, the fixture 202 is eliminated and replaced by a high temperature potting compound that seals and holds the wires 226 in place. Where the fixture 202 is used, it preferably is anchored to the segment 173 by an epoxy or potting compound.

In one preferred embodiment, at least one of the sensors 180, 182, 184, 186, 188, 190, 192, and 194 is a temperature sensor, such as an RTD, a thermocouple, or a

thermistor. Where measurement of absolute temperature in the refining zone is desired, a preferred temperature sensor is a platinum RTD that has three wires.

Where only the relative difference in temperature is needed, other kinds of temperatures sensors can also be used. Suitable examples include platinum RTD

5 temperature sensors; nickel, copper, and nickel/iron RTD temperature sensors; and thermocouples, such as J, K, T, E, N, R, and S thermocouples.

In another preferred embodiment, each of the sensors 180, 182, 184, 186, 188, 190, 192, and 194 is a pressure sensor, such as a ruggedized pressure transducer, which can be of piezoresistive or diaphragm construction and that is used to sense pressure in
10 the refining zone. An example of a pressure transducer that can be used is a Kulite XCE-062 series pressure transducer marketed by Kulite Semiconductor Products, Inc. of One Willow Tree Road, Leonia, New Jersey.

In still another preferred embodiment, the sensing assembly 196 or 200 is comprised of a combination of pressure and temperature sensors. For example, sensing
15 assembly 196 or 200 can be comprised of a single temperature sensor that senses temperature in the refining zone and a single pressure sensor that senses pressure in the refining zone. The sensing assembly 196 or 200 can also be comprised of a plurality of temperature sensors and a plurality of pressure sensors that sense temperature and pressure at different locations in the refining zone.

20 FIGS. 9-11 are directed to a method of controlling refiner operation. It has been long been assumed that a constant feed screw speed results in a constant volumetric flow rate of stock into a refiner and that a constant stock volumetric flow rate produces a

constant mass flow rate of fiber into the refiner. However, it has been discovered that the fiber mass flow rate can vary even when the feed screw speed and volumetric flow rate of stock remain constant. It is believed that these variations in fiber mass flow rate that occur when the feed screw speed is constant are caused by variations in the density of the fiber in the stock, namely changes in wood density, by variations in chip size, by variations in chip moisture content, by feed screw wear over time, by process upsets that occur upstream of the refiner, and by other reasons that are often specific to the mill in which the refiner is installed.

It is thus believed that these variations are caused by changes in consistency of stock entering the refiner. A method of this invention measures consistency near or in the refining zone. Consistency measurement can then be used to adjust mass flow to help keep the consistency of stock entering the refiner constant or nearly constant. For example, where and when variations occur, changes can be very quickly made to stock in the refining zone to make the consistency of stock in the refining zone more constant or closer to a desired consistency setpoint. One preferred way of making a change is to adjust the flow of dilution water. Another preferred way is to change feed screw speed.

In one preferred control method, refiner operation is affected by controlling the volumetric flow rate of stock entering the refiner in accordance with determined consistency (process variable) that preferably is based on, at least in part, at least one parameter that relates to conditions in the refining zone. Refiner process control is achieved by adjusting the volumetric flow rate of stock in response to changes in consistency relative to its setpoint.

By regulating the volumetric flow rate of the stock to keep the fiber mass flow more stable, the fiber bundles in the stock are impacted with a more constant specific energy. This leads to more consistent refining intensity, which greatly reduces variations in motor load and pulp quality. Because variations in motor load are reduced, less energy
 5 is used during refining.

In another preferred control method, refiner operation is affected by controlling the flow rate of dilution water entering the refiner in accordance with measured consistency that preferably is also based on, at least in part, at least one parameter that relates to conditions in the refining zone. Refiner process control is achieved by adjusting
 10 the rate of flow of dilution water in response to changes in consistency relative to its setpoint.

When either or both control methods are implemented in a primary refiner, variation in pulp quality measured as freeness, long fiber content, shives, etc. (CSF) can be reduced, the occurrence of shives can be reduced, load swings can be decreased,
 15 clashing of refiner disks can lessen, and a more uniform fiber distribution preferably is produced. When implemented in a secondary refiner, refiner load is more stable, the energy required for a given CSF target can be reduced, and the reject rate can be decreased. The result is lower Kraft usage and more consistent pulp quality that produces a fiber product with better and more consistent tear, tensile, burst, and drainage
 20 characteristics.

FIG. 9 is a graph with a line 230 that shows a generally linear correlation between a process variable and the volumetric flow rate of stock entering the refiner. In the case of

the graph shown in FIG. 9, the process variable is a temperature in the refining zone. The correlation strongly shows that, with all else remaining the same, the temperature in the refining zone substantially linearly increases with increasing volumetric flow rate of the stock resulting from increasing the speed of the feed screw. This correlation also holds
 5 true for pressure in the refining zone, as well as for the temperature at the refiner inlet and outlet.

There is also a generally linear correlation between the dilution water flow rate and consistency. As dilution water flow rate is increased, consistency decreases and vice versa.

10 FIG. 10 is a second graph of a pair of curves that depicts an inverse relationship between a process variable 232 and volumetric flow rate 234. In the case of the graph shown in FIG. 10, the process variable is temperature. FIG. 10 illustrates that when temperature drops, it can be increased by increasing the speed of the feed screw to increase the volumetric flow rate of stock entering the refiner. If it is assumed that the
 15 consistency of the stock entering the refiner remains constant, increasing the volumetric flow rate will generally increase the temperature (and pressure) in the refining zone and at the refiner inlet and the refiner outlet.

FIG. 11 is a third graph of a pair of curves that shows the relationship between the flow rate of dilution water 238 and a process variable 240 that preferably is a refining
 20 zone temperature. As dilution water flow rate is reduced, the temperature in the refining zone rises and vice versa. Thus, dilution water flow rate can be controlled to regulate refiner temperature. Dilution water flow rate can be controlled in addition to or in

combination with the feed screw speed.

FIG. 12 schematically depicts a preferred embodiment of the refiner control method 236. During operation, the processor 34 monitors refiner operation and obtains a process variable 242.

5 During operation, the processor 34 monitors a number of refiner parameters including main motor power, dilution water flow rate, and refiner disk pressure (hydraulic pressure). At least one of other parameter that is monitored is a parameter that relates to conditions in the refining zone. One preferred parameter is a temperature in the refining zone that can be an absolute temperature. Another preferred parameter is a pressure in the
10 refining zone that can be an absolute pressure. If desired, other parameters can also be monitored including refiner inlet and outlet temperatures and/or pressures. If desired, pressures and temperatures can both be monitored.

In one preferred embodiment, the process variable is a monitored parameter, such as a refining zone temperature and pressure. The process variable can also be a refiner
15 inlet or outlet temperature or pressure. In another preferred embodiment, the process variable is calculated using one of these monitored parameters.

In step 244, the process variable is compared with the setpoint to determine whether to adjust the volumetric flow rate of stock in step 246. In one preferred implementation, the process variable is compared with the setpoint, and the volumetric
20 flow rate is adjusted up or down depending on whether the process variable is greater than or less than the setpoint.

Referring to FIG. 13, in another preferred implementation, the process variable is

compared with the setpoint and the volumetric flow rate is adjusted if the process variable falls outside a first band 248 that lies above the setpoint and a second band 250 that lies below the setpoint. Where the process variable falls outside band 248, such as where indicated by reference numeral 252, the volumetric flow rate of stock is increased or decreased to bring the process variable back within the band. Likewise, where the process variable falls outside band 250, such as where indicated by reference numeral 254, the volumetric flow rate of stock is conversely increased or decreased to bring the process variable back within the band.

FIG. 14 depicts an implementation of the control method where a new setpoint is determined at step 256 when it has been determined that refiner operation has been changed in step 258. For example, should an operator change some particular aspect of refiner operation, a new setpoint will be determined. A new setpoint will also be determined if the aspect of refiner operation that was changed was done so automatically. For example, where there is a DCS linked to the refiner, the DCS can change some aspect of operation, such as main motor speed, that will cause a new setpoint to be determined.

After the new setpoint has been determined, at step 256, the controller 236 will resume obtaining the process variable and the rest of the algorithm shown in FIG. 14 will be carried out. To permit the refiner operation to stabilize, preferably, some time passes before the new setpoint is determined.

FIGS. 15 and 16 illustrates a preferred method of determining a new setpoint. The first vertical line labeled reference numeral 260 represents when refiner operation has been changed. The second vertical line labeled reference numeral 262 represents when

the refiner operation has stabilized after the change, and the new setpoint has been determined. Referring to FIG. 16, in one preferred implementation, the process variable is obtained in step 264, and the process variable obtained is analyzed to determine whether its magnitude over time has stabilized in step 266. In determining whether refiner

- 5 operation has stabilized, successive process variables are analyzed to determine whether their change in slope is less than 5%. In another method of determining whether refiner operation has stabilized, each process variable of a current cycle is compared to its value from the prior cycle for a number of cycles that can be two cycles in number, three cycles in number, or more. If the absolute value of the average of the current process variable
- 10 value and its prior value for at least two cycles is compared, the process will be deemed converged, *i.e.*, steady state, if the averages fall within some acceptable tolerance. For example, where three consecutive temperatures are 171.5°, 170.5°, and 170.0°, and the tolerance 0.5°, convergence will not have occurred because the absolute value of the averages will not have fallen with the 0.5° tolerance. In another example, where the three
- 15 consecutive temperatures are 170.5°, 170.0°, and 170.0°, and the tolerance 0.5°, convergence will have occurred because the absolute value of the averages will have fallen with the 0.5° tolerance. When it has been determined that refiner operation has stabilized, the controller is released, and its control over mass flow resumes.

FIG. 17 illustrates another flow chart of another preferred controller

- 20 implementation. If it is determined in step 244 that an adjustment to mass flow is needed, the volumetric flow rate of the stock entering the refiner 32 is adjusted in step 268. For example, if the process variable has dropped below the setpoint such that adjustment is

needed, the volumetric flow rate of stock entering the refiner 32 can be appropriately increased or decreased. If the process variable has risen above the setpoint such that adjustment is needed, the volumetric flow rate of stock entering the refiner 32 can be appropriately conversely increased or decreased.

5 As an example, where the process variable is a refiner temperature, such as temperature in the refining zone, the volumetric flow rate will be increased if the temperature has risen far enough from a setpoint temperature such that adjustment is needed. The volumetric flow rate will be decreased if the temperature has dropped far enough below the setpoint temperature such that adjustment is needed.

10 Changing the volumetric flow rate preferably is accomplished by speeding up or slowing down the feed screw. Increasing the feed screw speed will increase the volumetric flow rate, and decreasing the feed screw speed will decrease the volumetric flow rate.

 In some instances, changing the volumetric flow rate of stock entering the refiner
15 will not have the desired affect of converging the process variable to its setpoint. This failure can be caused by changes in the mass flow rate of fiber entering the refiner that occur independently of the volumetric flow rate of the stock. It is believed that this occurs because the density of the fiber in the stock has changed, chip size has changed, chip moisture content has changed, the feed screw has become worn over time, process upsets
20 have occurred upstream of the refiner that affect fiber mass flow, or due to other reasons that are often specific to the mill in which the refiner is installed.

 To account for the possibility of the fiber mass flow rate changing independent of

the volumetric flow rate of the stock, step 270 determines whether the process variable continues to diverge from the setpoint despite the volumetric flow rate of the stock having been adjusted in step 268. If it is determined that the process variable is diverging from the setpoint too much, the flow rate of the dilution water is adjusted in step 272.

- 5 For example, where the process variable continues to diverge despite adjustment of the stock mass flow rate by a certain amount or by a certain percentage, the dilution water flow rate will be changed. For example, if the process variable continues to diverge and goes outside of an acceptable band, the dilution water flow rate can be changed. Hence, if the process variable is greater than or less than the setpoint by a certain
- 10 percentage, such as 5%, the dilution water flow rate can be adjusted.

- The dilution water flow rate is increased or decreased depending on the direction of convergence of the process variable. Where the process variable is a refiner temperature, such as a temperature in the refining zone, the dilution water flow rate is increased if the temperature increases above the setpoint and continues to diverge from
- 15 the setpoint such that dilution water flow rate adjustment is needed. Conversely, the dilution water flow rate is decreased or stopped if the temperature decreases below the setpoint and continues to diverge unacceptably from the setpoint. This relationship also holds true for refiner pressure, such as a pressure in the refining zone.

- FIG. 18 illustrates a still further preferred implementation of the control method.
- 20 A first process variable is obtained in step 242. It is determined whether refiner operation has changed in step 258. If so, control is put on hold in step 274 until refiner operation stabilizes. Step 258 is not order dependent and can be performed anytime during

execution of the control algorithm depicted in FIG. 18.

The first process variable and/or a second process variable can both be monitored to determine when one, the other, or both have reached a steady state value, such as in the manner depicted in FIGS. 15 and 16. When it has been determined that one or both
5 process variables have reached a steady value, the steady state value is taken as the new setpoint and control resumes.

If refiner operation has not changed, the first process variable is compared against its setpoint in step 244 to determine whether the volumetric flow rate of stock entering the refiner should be adjusted. If so, the volumetric flow rate of the stock is changed in
10 step 266. If not, the control algorithm branches to step 242 where the first process variable is once again obtained.

If the volumetric flow rate of the stock has been adjusted, a second process variable is obtained in step 276. If desired, both process variables can be determined at the same time or in a common control algorithm step.

15 The second process variable is compared against its setpoint in step 278 to determine whether an additional mass flow rate adjustment is needed. If so, the additional flow rate adjustment is performed in step 280. Preferably, the flow rate adjustment performed is an adjustment of the flow rate of dilution water to the refiner. If no flow rate adjustment is required, the control algorithm returns to obtain one or both process
20 variables.

The control algorithm implementation depicted in FIG. 19 is similar to the control algorithm depicted in FIG. 18 except that the second process variable is compared against

its setpoint in step 278 even if it has been determined that no mass flow rate adjustment is needed in step 244. This arrangement enables, for example, two control loops to be executed at the same time. It also enables two completely independent control loops to be used.

5 In one preferred implementation of the control algorithms depicted in FIGS. 18 and 19, the first process variable preferably is a refiner temperature or a refiner pressure and the second process variable preferably is consistency. Where refiner temperature and/or pressure are used as a process variable, a temperature or pressure in the refining zone preferably is obtained.

10 FIG. 20 illustrates a control block diagram of a preferred controller 274 that can be used with any of the preferred implementations previously discussed. While the controller can be a proportional controller, it preferably has at least a proportional component and an integral component. Where it is desirable to, for example, use feedforward control, the controller 274 can also have a derivative component.

15 At summing junction 282, the setpoint at the selected set of refiner operation conditions is summed with a process variable from a feedback loop 284 that is obtained from some parameter relating to the process 286 being controlled, namely refiner operation. The result of the summing junction produces e , which is set forth below:

$$e = SP - PV \quad (\text{Equation I})$$

20 where e is the error, SP is the value of the setpoint, and PV is the value of the process variable.

5 the controller can be expressed by the equation:

(Equation II)

the controller can be expressed by the equation:

(Equation III)

where $u_l(t)$ is the output of this portion of the controller. Where present, the derivative action of the controller can be expressed by the equation:

(Equation IV)

where $u_D(t)$ is the output of this portion of the controller.

(Equation V)

where $u_D(t)$ is the output of this portion of the controller.

The controller output, $u(t)$, gets communicated as a control signal to the particular component being regulated by the controller. For example, where the component being regulated is the volumetric flow rate of stock, the control signal can be sent directly to a feed screw motor or motor controller that controls the feed screw speed. Where the system includes DCS, the signal preferably is sent to the DCS and causes the DCS to adjust the feed screw speed. Where the component is dilution water flow rate, the signal

can be sent directly to a dilution water pump motor or motor controller that controls the dilution water pump. Where the system includes a DCS, the signal preferably is sent to the DCS and causes the DCS to adjust the dilution water flow rate. If desired, the output, $u(t)$, can be processed further to produce the control signal or otherwise used in obtaining

5 the control signal.

Because each refiner, stock system arrangement, and fiber processing plant is different, it is believed very likely that the controller will have to be tuned for the particular refiner it will be used to control. One preferred tuning method subjects the refiner to a step input and analyzes the response. More specifically, the controller is tuned

10 to determine the controller gain, K_c , the integral time constant, T_i , and, where a derivative component is used, the derivative time constant, T_d , by analyzing system response in response to a step input. In one preferred controller, the controller is a proportional-integral controller that has no derivative control component.

For example, where the controller output, $u(t)$, is used to control the volumetric

15 flow rate of stock entering the refiner and the refiner temperature is the process variable, the parameters K_c , T_d , and T_i , can be determined by increasing the volumetric flow rate of stock by a step input of a specific magnitude and then monitoring how fast it takes for the refiner temperature to begin increasing, as well as how long it takes until before the temperature reaches a steady state condition and its magnitude at steady state. This

20 information is used in determining the dead time, T_{DEAD} , of the system, the time constant, T_i , the process gain, K , and the controller gain, K_c . The dead time, T_{DEAD} , is used to determine the controller gain, K_c , and can be used to determine the time constant, T_i .

Where the output, $u(t)$, is used to control the dilution water flow rate entering the refiner and consistency is the process variable, the parameters K_c , T_d , and T_i , can be determined by increasing the dilution water flow rate by a step input of a specific magnitude and then monitoring how fast it takes for the consistency to begin decreasing, as well as how long it takes until before the consistency reaches a steady state condition. The magnitude of the consistency at steady state is also determined. This information is used in determining the dead time, T_{DEAD} , of the system, the time constant, T_i , the process gain, K , and the controller gain, K_c .

In one preferred embodiment, the process variable is refiner temperature and the output of the controller is used to set the speed of the feed screw to control the flow rate of stock entering the refiner. The controller must be tuned for the specific refiner and fiber processing plant in which the refiner is installed.

In one preferred method of tuning the controller, the system dead time, T_{DEAD} , the time constant, T_i , of the system, and the process gain, K , are determined. In tuning the controller, the refiner is operated normally at a particular set of operating conditions until steady state operation is achieved. Referring to FIG. 15, where the feed screw speed is the controlled variable 288, the speed is then adjusted upwardly or downwardly by an amount (represented by the step in FIG. 15) that preferably is measured. Then, the time it takes from the moment of the adjustment for the change in feed screw speed (controlled variable) until temperature (process variable) is affected is measured. This amount of time, the lag between changing the output and the change affecting the process variable, is the dead time, T_{DEAD} .

Where refiner temperature is the process variable and the feed screw speed is being controlled, T_{DEAD} can be as little as one second to as much as about two minutes, depending on the refiner, how far the feed screw is located from the refiner, and other factors. Typically, T_{DEAD} is between about five seconds and about fifty seconds. Where
 5 consistency is the process variable and the dilution water flow rate is being controlled, T_{DEAD} is less and typically is between one half second and five seconds.

Referring once again to FIG. 15, the time constant, T_i , is determined by measuring the time it takes for the process variable to reach about 2/3 (about 63.2%) of the difference between its minimum value and its maximum steady state value. Where
 10 temperature is the process variable and volumetric flow rate (feed screw speed) is the controlled variable, the time constant, T_i , ranges between 0.3 minute and 1.1 minute. Typically, the time constant, T_i , ranges between about 0.4 minute and about 0.75 minute. Where consistency is the process variable and dilution flow rate is the controlled variable, the time constant, T_i , is smaller and typically less than about 0.3 minute.

15 The controller gain, K_c , is determined or selected. K_c preferably ranges between about 0.25 and about 2. Where the controller is a PID controller, the derivative time constant, T_d , can be set approximately equal to a rate of change of the process variable after the dead time has passed but before it has reached steady state.

In one preferred method of determining K_c , the process gain, K , is first determined
 20 and then used, along with the dead time, T_{DEAD} , and the time constant, T_i , to determine K_c . Referring to FIG. 15, K is the ratio of the change (or percent change) in the magnitude of the step input over the change (or percent change) in the magnitude of the output, *i.e.*,

max - min.

Where the controller is a PI controller, the following equation can be used to determine the proportional band, PB , in percent:

$$PB = 110 \frac{KT_{DEAD}}{T_i} \quad (\text{Equation VI})$$

- 5 The coefficient of 110 can be varied depending on the characteristics of the controller desired. The controller gain, K_c , is then determined using the following equation:

$$K_c = \frac{100}{PB} \quad (\text{Equation VII})$$

Where this method is used, the following equation can be used to determine the time constant, T_i , in minutes:

$$10 \quad T_i = 3.33 T_{DEAD} \quad (\text{Equation VIII})$$

Where the controller is a PID controller, the following equation can be used to determine the proportional band, PB , in percent:

$$PB = 80 \frac{KT_{DEAD}}{T_i} \quad (\text{Equation IX})$$

- The coefficient of 110 can be varied depending on the characteristics of the controller desired. The controller gain, K_c , is determined in the manner set forth above in Equation VII. The following equation can be used to determine the integral time constant, T_i , in minutes:

$$T_i = 2.00 T_{DEAD} \quad (\text{Equation X})$$

- The following equation can be used to determine the derivative time constant, T_d , in minutes:
- 20

$$T_d = 0.50T_{DEAD} \quad (\text{Equation XI})$$

FIG. 21 depicts a pair of the controllers 274 that control the same refiner. The process of the refiner being monitored in one controller arrangement, referred to by reference numeral 290, is an actual refiner temperature, preferably a temperature in the refining zone. Where there is more than one sensor, such as sensors 78, 180, 182, 184, 186, 188, and 190, from which an actual refining zone temperature can be obtained and used as the process variable 284, the refining zone temperature can be an average temperature, the temperature of a single selected sensor, or a temperature of the refining zone obtained using another method.

The actual temperature is summed at 282 with a desired temperature setpoint to obtain the process error value, e . The process error value, e , is fed into the controller 274. The controller 274 outputs a signal that is used to regulate the speed of the feed screw to regulate the volumetric flow rate of stock entering the refiner. Where the actual temperature has risen above the desired temperature, the controller 274 will output a signal 292, labeled "Production Feed/Control" in FIG. 21, that will decrease the speed of the feed screw to lessen the volumetric flow rate. Where the actual temperature has dropped below the desired temperature, the controller 274 will output a signal 292 that increases the speed of the feed screw to increase the volumetric flow rate.

The process variable of the refiner being monitored in the other controller arrangement, referred to by reference numeral 294, is a consistency measurement, referred to in FIG. 21 as "Actual Consistency." The measured consistency is summed at 282 with a desired consistency setpoint to obtain the process error value, e . The process

error value, e , is fed into the controller 274. The controller 274 outputs a signal 296 that is used to control operation of the dilution water pump to regulate the flow rate of dilution water entering the refiner. Where the measured consistency has risen above the desired consistency, the controller 274 will output a signal 296, labeled "Dilution" in FIG. 21,
 5 that will increase the dilution water pump output to increase the dilution water flow rate. Where the actual consistency has dropped below the desired consistency, the controller 274 will output a signal 296 that decreases or stops the dilution water pump to thereby reduce the dilution water flow rate.

In another preferred method, the measured consistency is the process variable and
 10 the controller output is a control signal that controls or is used to control the feed screw speed to control the volumetric flow rate of stock entering the refiner. In a still further preferred method, at least one measured temperature, *e.g.*, the actual temperature, in the refining zone is the process variable and the controller output is a control signal that controls or is used to control the flow of dilution water.

15 Where the refiner is a twin refiner, the first controller arrangement 290 preferably is used to control the volumetric mass flow rate of stock entering a primary refiner of the twin refiner. The process variable measured is temperature in a refining zone of the primary refiner. The second controller arrangement 294 is used to control the flow rate of dilution water into a secondary refiner of the twin refiner. The process variable measured
 20 is the consistency of the stock at the output of the primary refiner or the inlet of the secondary refiner of the twin refiner. Where consistency is measured in the refining zone, it can be measured in a refining zone of the primary refiner or the secondary refiner.

Where consistency is measured in a refining zone of the secondary refiner, it preferably is measured adjacent where the stock enters the refining zone.

Where consistency is the process variable, the consistency is measured of the stock entering the refiner. In such an instance, temperature and/or pressure sensor(s) preferably are located in the refiner such that it can measure the consistency of the stock before or when it enters a refining zone or when it is in a refining zone.

Referring additionally to Figs. 23-30, in one preferred method of measuring or determining consistency, refiner temperature or pressure measurements are used along with measurements of other refiner parameters to measure consistency. This novel method of determining consistency and system used to determine consistency is based on an application of mass and energy balance to the pulp as it flows through the refiner 32. Moisture in the refiner 32 is assumed to be an equilibrium mixture of water and steam, and the temperature (and therefore, pressure) of the water-steam mixture is assumed to vary with radial position in the refiner 32. Steam is assumed to be saturated throughout the refining zone.

The inputs required for the computation of consistency include the temperature within the refiner zone (or pressure), the distribution of the motor load (specific power) within the refining zone, and an initial consistency. Initial consistency can be an assumed value or provided in a conventional manner. In one preferred implementation, initial consistency is an estimated value. As an output, consistency is provided as a function of radial position in the refiner.

The consistency determination procedure set forth below is well suited for use in

controlling refiner operation, since the refining zone temperature, refiner load, dilutions, hydraulics and other refiner parameters are measured in real time. Using this method of determining consistency in real time, monitoring and/or controlling refining zone consistency as a function of both time and space (e.g., location in the refining zone) can
5 be done. Consistency can be quickly measured in no more than five minutes and preferably is measured in real time. In one preferred embodiment, consistency is measured a plurality of times a second and preferably at a rate of twenty times a second.

A challenge in the refining industry is that quality needs to be improved and production costs need to be reduced. This has been true for the TMP process almost
10 since its introduction some 30 years ago. However, today the challenge that lies ahead for the TMP process is even more real because of the increased supply of DIP, its relatively low value, and the restructuring of the market place. The reality is that only the strongest and most efficient installations will survive as the 21st century begins.

Efficiency can be improved significantly by reducing the variation in important
15 process parameters such as applied specific energy. By reducing the variations in the process, the resulting variations in pulp and paper quality will be reduced as well.

The advancement in computer technology and computational techniques has furthered knowledge of the refining process. Using proprietary software in conjunction with specially developed sensors, a refining modeling technology has been developed
20 which is based on fundamental laws.

This technology is now used in real time for control purposes, and with the use of the above identified sensor refiner plate 173, an example of which is shown in FIG. 7,

with one or more embedded sensors 180-194, significant process improvements are achieved.

Using a method and system of this invention, temperature and/or pressure measurements can be made and preferably are made in real time. Preferably,

5 measurements can be made at a rate of at least one every five minutes and preferably a plurality of times per second or faster. Using a method and system of this invention, control changes can be made and preferably are made to the refiner 32 in real time.

Preferably, they can be made at a rate of at least one every five minutes and preferably faster. For example, in one preferred embodiment, real time control of the refiner 32 is
10 achieved. Preferably, the system and method enables a plurality of the aforementioned setting changes to be made per second and as fast as at a rate of about twenty hertz.

A refiner control method of this invention reduces the process and quality variations in commercial size disc refiners. The theory behind the control system will be explained first, followed by a system description. The discussion concludes with a
15 discussion on the impact of important process parameters on the resulting pulp quality.

The concept of control system shown in the drawing figures is to enhance the performance of a disc refiner 32 through controlled refining operation. See, e.g, FIGS. 1-5, 7, 12-22, and 27. This is accomplished by expanding existing refiner plate technology to include sensors, which can be used to describe and control the refining conditions as a
20 function of time and space (e.g., location).

The key to understanding the process of mechanical pulping in refiners is through

an analysis of how the power supplied to the refiner 32 is transferred to the wood and the water it contains. FIG. 23 illustrates how mechanical power is transferred to wood and water in the refining zone 304 through the geometry of a pair of refiner plates 136, 138. FIG. 23 also graphically depicts equivalent elastic strain that the refiner plates 136, 138 impart to fiber 304 being refined in the refining zone 306.

A precise macroscopic analysis would require a precise energy budget. This implies that a precise accounting of the total energy supplied to the refiner must be made in terms of the difference in the energy content of the wood, steam and water entering and leaving the refiner 32. This is not an easy task given that energy can be stored in various forms.

Despite these seemingly very difficult obstacles, a few simplifying, and not unreasonable, assumptions can make the application of the energy principle practically feasible. These assumptions have their basis in the pulping process, and therefore an explanation of the assumptions is provided below.

Broadly speaking, the energy stored in the wood and the water/steam is of three forms:

(a) Kinetic energy. Kinetic energy is the energy a system has by virtue of the bulk (macroscopic) motion of its constituents. During steady state refiner operation, throughput is constant (short term) and consequently the change in kinetic energy of the wood and water across the refiner is an unimportant contribution. Moreover, feed rates are such that the velocity of the wood and water are small enough that they store an insignificant amount of kinetic energy. The significant source of kinetic energy is that

present in the steam that leaves the refiner. This kinetic energy however is generated through conversion of the internal and potential energy of the produced steam. Therefore, kinetic energy preferably can be neglected in an energy budget that accounts for the production of steam.

- 5 (b) Potential energy. Potential energy is the energy present in the system by virtue of its position relative to a force field. Potential energy comes in various forms. The least important form is gravitational potential energy, which can straightaway be neglected because elevation change in the entire process is negligible. Strain energy is the elastic energy stored in a body when it has been deformed under the action of applied forces.
- 10 This energy is completely recovered when the applied forces are removed. A strong case can be made for neglecting the potential energy in the system because it has very non-linear behavior and, like metals, exhibits permanent deformation when compressed beyond a certain point.

When wood is compressed, initial stress-strain behavior is linear. The energy

15 stored during this period is strain energy and is recoverable. When the load is high enough, a form of yielding occurs and the stiffness of the wood decreases. FIG. 24 is a typical load-deflection (stress-strain) curve for wood and it shows that only a small portion of the energy is actually lost. FIG. 24 illustrates the following relationship: as the refining gap is reduced, both stress and strain increase. It also illustrates that hysteresis

20 occurs.

Therefore, when wood is crushed it is fair to assume that only a small portion of the energy supplied can be recovered.

Since wood, like ductile metals, is relatively tough in compression, it can be concluded that only a small amount of the energy supplied to compress the wood will be
5 stored as surface energy. On the basis of the above arguments, both the strain energy and surface energy preferably can be neglected.

Water too can have strain energy, but since it is in a freely flowing environment, rather than an enclosed environment, it is unlikely to contain much strain energy.

Thus, the potential energy of a system consisting of the wood chips and water can
10 be neglected.

Internal energy is the energy associated with 'heat' and is the energy that a system has by virtue of its temperature. Internal energy is commonly called heat and is manifested in a temperature rise in the system.

In the pulping process, there are likely to be only small increases in kinetic and
15 potential as explained above. Therefore, in accordance with the first law of thermodynamics, the work done by the refiner 32 must increase the internal energy of the system or be dissipated as heat. In a refiner 32 there is little scope for heat dissipation because of the tremendous rate at which energy is supplied to the refining zone 306. Actually, direct observation indicates that most of the "heat dissipation" occurs when
20 steam generated during pulping leaves the refining zone 306.

Thus, the key conclusion that may be drawn from the argument presented above is that most of the work done by the refiner 32 is converted to internal energy of the wood-and-water system before it leaves the refining zone 306.

The internal energy comes from two main components of the work done by the refiner. These are (1) the work required for permanent deformation of the wood and (2) the work done to overcome friction in all its forms (wood against wood, viscous resistance offered by the water, refiner segments against wood and water etc). A smaller contribution is made by the inherent viscoelastic and viscoplastic nature of the wood itself.

Thus, the end result is an increase in the temperature of the system because of the increase in internal energy. FIG. 25 illustrates a typical temperature profile in the refining zone in a single disc high consistency refiner.

Typically, the temperature in high consistency refiners rises enough that the moisture in the wood is converted to steam, making the pulp drier than the incoming chips. The steam generated is confined to the cramped refining zone and therefore its pressure builds up, which leads to an associated rise in temperature.

The principle of conservation of energy, also called the first law of thermodynamics states:

$$Q + W = \Delta KE + \Delta PE + \Delta U \quad (\text{Equation XII})$$

This law applies to a closed system, i.e., a system with constant mass. Q is the heat transferred to the system, W is the work done on the system, KE is the kinetic energy, PE

is the potential energy, U is the internal energy, and the Δ symbol represents change or increment.

Using the argument from the previous section, the first law can be approximated for the wood-water system in the refiner 32. The changes in kinetic and potential energy
 5 are small relative to the internal energy and the heat transferred to/from the system is small compared to the work done by the refiner. This gives

$$W = \Delta U \quad (\text{Equation XIII})$$

In a process or flow-based system, it is much more convenient to operate in terms of time rates of change of work, heat and energy. Thus, if the power supplied to the
 10 refiner 32 is P , then the work done by it in a time increment Δt is $P\Delta t$ and the change in internal energy of the wood-water system will be

$$P\Delta t = \Delta U$$

$$P = \frac{\Delta U}{\Delta t} \quad (\text{Equation XIV})$$

As time approaches zero, a true rate equation is obtained:

$$P = \frac{dU}{dt} = \dot{U} \quad (\text{Equation XV})$$

15 Technically, Equation XV applies to the pulping process, but it cannot be applied directly because the refining zone 306 is an open system, defined by a fixed volume in space with material crossing the boundaries of the volume. Such an open system is also called a control volume. In order to use it, two corrective terms need to be added to account for the influx and outflux of energy across the boundaries of the refining zone.

20 The corrected equation is:

$$P + \dot{U}_{in} = \dot{U} + \dot{U}_{out} \quad (\text{Equation XVI})$$

The subscripts *in* and *out* refer to influx and efflux respectively. U now represents the internal energy within the refining zone 306. The equation above is applicable to any open system and this includes an open system of infinitesimal dimensions.

- 5 After putting the terms above in the energy equation and neglecting products of infinitesimals, it is reduced to the form:

$$\begin{aligned} 2\pi r \bar{W} dr = 2\pi r L m_s dr + \dot{m} H_s dT + \\ \dot{m} \frac{1-C}{C} H_l dT + 2\pi r m_s H_l T dr + \quad (\text{Equation XVII}) \\ \dot{m} H_l T d \frac{1-C}{C} \end{aligned}$$

The last two terms in the equation above sum to zero because of conservation of mass. The remaining terms can be rearranged to give

$$10 \quad m_s = \frac{1}{L} \left(\bar{W} - \frac{\dot{m}}{2\pi r} \left[H_s + \frac{1-C}{C} H_l \right] \frac{dT}{dr} \right) \quad (\text{Equation XVIII})$$

Thus, the application of mass and energy conservation to the open system containing moist wood yields two equations for the consistency and the steam production rate, respectively, in the refining zone 306. These equations are:

$$\begin{aligned} \frac{dC}{dr} = 2\pi r \frac{m_s}{\dot{m}} C^2 \\ m_s = \frac{1}{L} \left(\bar{W} - \frac{\dot{m}}{2\pi r} \left[H_s + \frac{1-C}{C} H_l \right] \frac{dT}{dr} \right) \end{aligned} \quad (\text{Equations XIX and XX})$$

- 15 The temperature and specific power can be obtained through direct measurement.

FIG. 26 is a typical plot of the refining zone temperature as a function of radius. In the

segment 173 shown in FIG. 7, sensors at different radial positions provide the required information.

Referring to FIG. 27, signals from the sensor segment 173 are fed into a PC computer, such as that depicted by reference numeral 38, for analysis and control. By attaching system 30" as a "transmitter," all interlocks and logic are kept in the DCS 94. Keeping the interlocks on both sides (system 30" and DCS 94) ensures a fail-safe communication between the two.

The system 30" used in determining consistency consists of four major components shown in FIG. 27. The system includes sensor segment 173, signal conditioners 86, a PC based control box 38, and a remote monitor/keyboard 48. The system 30" communicates with the mill DCS system 94 through analog and digital signals 92, just like other process transmitters.

The refiner plates are equipped with a sensor array 70, which sends the process conditions to the signal conditioners 86, located in a electrical box outside the refiner 32. Analog signals (4-20 mA) are then fed to the PC control box 38, where the signals are analyzed and a new control output 92 is computed. The control output 92 from the system 30" arrives at the DCS as a remote setpoint, commonly referred to as a cascade mode. A user interface can be provided through a remote terminal 48.

Referring to FIGS. 22 and 28, the operator retains total control of the refiner 32 through a unique "hold" protocol between the DCS 94 and the system 30".

If for example the operator would like to adjust the specific energy applied by reducing the amount of dilution water, the controller 274 of the system 30" is temporarily

put on hold. The hold is kept until a new steady state process value has been reached, and then the controller is released with this process value as a new set point. As a result of the "hold" function, the operator and the controller of the system 30" will not compete for the desired set points. The operator decision overrides the controller of the system

5 30".

The control loops used preferably are conventional PID controllers that are easily customized to fit specific needs. Several individual refiners can be controlled independently using the same system 30".

Figure 29 is a typical graph of the refiner control system 30" operating in
10 production control by maintaining a constant refining zone temperature distribution. The difference between control mode and manual mode is shown in the example of Figure 29 as a dashed line. In control mode, the motor load is stable between 13.9-14.1 MW over the period shown. For the same period, the refiner control system 30" varies the feed screw rate between 61.5% to 62.7%. The controller 274 needs to change the screw speed
15 in order to maintain a set point of 178°C. Because refining zone temperature is constant, a constant motor load is maintained. Once the controller is switched to manual mode (constant feed screw speed), both motor load and refining zone temperature vary significantly.

The change in raw material can clearly be seen in FIG. 30 when operation is
20 observed over a longer period.

Trials have also been conducted to investigate what impact the reduced variation in refiner operation has on the resulting pulp quality. Table 1 below lists the standard

deviation of CSF results in a study where two parallel Andritz TWIN 60 inch refiners are compared. Approximately 70 composite primary blow-line samples were collected over a 48 hour period.

	Line A	Line B	A-B Difference
Line B in manual	11.7	11.1	5%
Line B in control	28.7	3.7	87%

5

Table 1

The standard deviation of the blow line freeness was virtually identical when both primary refiners were operating in manual. Repeating the trial with line B in control however, reduced the variation by 87%.

10 A refiner control system 30", which is based on fundamental physical laws, was described above. The consistency and the steam generated in a refiner 32 can be calculated by applying conservation of mass and energy.

The application of these principles is based on the argument that a majority of the power input to the refiner 32 appears in the form of heat that raises the temperature in the refining zone and produces steam. As input, the method preferably requires an array of sensors 70 within the refining zone 306.

15

By controlling the refining zone temperature the operating stability of the TMP system is greatly improved. As a consequence, the resulting freeness variation is significantly reduced.

20

Mathematical theory and equations behind the method are disclosed below :

The model is based on the following two equations for conservation of mass and energy, respectively:

$$\frac{dC}{dr} = 2\pi r \frac{m_s}{\dot{m}} C^2$$

(Equation XXI)

$$m_s = \frac{1}{L} \left(\bar{W} - \frac{\dot{m}}{2\pi r} \left[H_s + \frac{1-C}{C} H_l \right] \frac{dT}{dr} \right)$$

(Equation XXII)

The physical quantities that correspond to the variables in the above equations are listed in Table 2 below:

Symbol	Description	Units
C	Consistency	Dimensionless
m_s	Specific steam generation rate	kg/m ² -sec
\dot{m}	Dry wood throughput	kg/sec
R	Radial position	M
L	Latent heat of steam	KJ/kg
\bar{W}	Specific power	KW/m ²
H_s	Wood heat capacity	KJ/kg-°C
H_l	Water heat capacity	KJ/kg-°C
T	Temperature	°C

TABLE 2

One or more of the following inputs preferably are used in determining consistency: the refiner main motor power, the force exerted on the refiner disks urging them together (or hydraulic pressure or force), the dilution motor power of the refiner for each dilution pump, the refiner case pressure, the refiner inlet pressure, the chip washing water

5 temperature, the dilution water temperature, as well as the gap between refiner disks.

The consistency, C , is determined as a function of radial position in the refining zone 306. The temperature, T , is a temperature of stock preferably in the refining zone 306 or upstream of the refining zone 306. Where the temperature, T , is measured upstream of the refining zone 306, it preferably is measured slightly upstream of the

10 refining zone 306, such as immediately before the location where stock enters the refining zone 306. If desired, the temperature, T , can be measured at the refiner inlet 114 where stock enters the refiner 32. Where the temperature, T , is a temperature in the refining zone 306, it preferably is measured at or adjacent where stock enters the refining zone 306. The temperature, T , can be measured anywhere in the refining zone 306. Where a refiner 32

15 has more than one opposed pair of refiner disks, the temperature, T , preferably is taken upstream of the radially innermost pair of refiner disks or in its refining zone.

Where a sensor refiner disk or disk segment 173 is used, temperature, T , can be a temperature measurement from a single sensor, such as sensor 180, 186, or 194, or an average temperature determined from temperature measurements taken from a group of

20 sensors, such as sensors 194, 192 and 190 (or all of the sensors). Where it is desired to measure temperature, T , in the refining zone 306 adjacent where stock enters, sensor 190, 192 or 194 can be used. Preferably, the temperature measurement from sensor 194 is used

in such a case.

If desired, the temperature, T , can be determined using a combination of a temperature of stock entering the refiner 32 and a temperature of stock in the refining zone 306. One such example is an average temperature of the average of the temperature
 5 of stock entering the refiner 32 and a temperature of stock in the refining zone 306.

The latent heat of steam, L , is obtained from steam tables known in the art. The latent heat, L , is obtained for the temperature, T , that is measured. The specific power, \overline{W} , is determined by dividing the power input into the refiner 32, typically in megawatts, by the refiner disk surface area, in square meters.

10 The specific steam generation rate, m_s , is determined using an energy balance that assumes that all energy inputted into the refiner is converted to heat. Thus, it is assumed that the specific power, \overline{W} , of the refiner is converted into heat and known steam tables (not shown) are used to determine the specific steam generation rate using this assumption. Where implemented as part of an algorithm that is executed by a processor,
 15 one or more steam tables are utilized as lookup tables.

The wood heat capacity, H_s , is taken from a known wood heat capacity table based on the temperature of the chips measured before the stock enters the refiner 32. The water heat capacity, H_l , is also taken from a known table of water heat capacities and is based on the temperature of the water in the stock measured before the stock enters the
 20 refiner 32.

If the temperature, T , and the specific power, \overline{W} , are known as functions of radial

position, the two equations above can be combined to produce a non-linear ordinary differential equation (ODE) of first order for the consistency, C . This equation is:

This non-linear 1st order ODE can be converted into a linear 1st order ODE by noting that:

$$-\frac{1}{C^2} \frac{dC}{dr} = \frac{d}{dr} \left(\frac{1}{C} \right) = \frac{d}{dr} \left(\frac{1-C}{C} \right)$$

5

(Equation XXIII)

Accordingly, by defining a new variable Z as $(1 - C)/C$, the following linear order 1st order ODE results:

$$\frac{dZ}{dr} = \frac{H_l}{L} \frac{dT}{dr} Z + \frac{1}{L} \left(H_s \frac{dT}{dr} - \frac{2\pi r}{\dot{m}} \overline{W} \right)$$

10

(Equation XXIV)

This equation is of the general form:

$$\frac{dZ}{dr} = f(r)Z + g(r)$$

(Equation XXV)

15

From ODE theory, a general solution to the above equation is:

$$Z(r) = Ae^{\int f(r)dr} + e^{\int f(r)dr} \int g(r)e^{-\int f(r)dr} dr$$

(Equation XXVI)

The solution for this specific problem is easily obtained upon substitution of the

- 5 appropriate functions $f(r)$ and $g(r)$ into the equation above. A is an arbitrary constant that is determined from the initial condition, *i.e.*, the value of consistency (and therefore Z) at the inlet to the refiner. The final solution for Z is given below

$$Z(r) = Z(r_i) \left(\frac{L(r)}{L(r_i)} \right)^{\frac{H_l}{\beta}} + \frac{H_s}{H_l} \left[\left(\frac{L(r)}{L(r_i)} \right)^{\frac{H_l}{\beta}} - 1 \right] - \frac{2\pi}{\dot{m}} L(r)^{\frac{H_l}{\beta}} \int r \overline{W}(r) L(r)^{\left(\frac{H_l}{\beta} - 1 \right)} dr$$

10

(Equation XXVII)

This solution is based on the assumption that the latent heat of steam ($L(r)$) is a linear function of temperature of the form:

$$L(r) = \alpha + \beta T(r)$$

(Equation XXVIII)

15

The inlet radius is r_i . Since the temperature and the specific power are obtained at discrete points, the quadrature (last term in the equation for Z) is a function of the fitting

or interpolation procedure used to obtain the measured quantities as continuous functions of radial position. Once the fitting or interpolation functions (α and β) are known, the integration can be carried out numerically.

Finally, the consistency can be obtained from $Z(r)$ as:

$$C = \frac{1}{1 + Z}$$

5

(Equation XXIX)

This method preferably is implemented in software or firmware to compute the consistency. A piecewise linear interpolation function preferably is used for the temperature and specific power functions, which provides the advantage that the quadrature in the functional representation of $Z(r)$ can be exactly evaluated. Doing so, assumes that both the temperature and specific power data is available at the same radial locations.

Such a software or firmware implemented algorithm preferably can compute the consistency as a function of radial position. Only one measurement of consistency, C , is needed by the controller 274 shown in FIGS. 20 or 21. In one preferred implementation of this method, the consistency, C , determined is the consistency at the inlet of the refining zone or adjacent a radial inward location of the refining zone.

FIGS. 22 and 28 graphically illustrate a controller 274 being put on hold when an operating parameter of the refiner 32 is changed. The controller 274 is released after

the operating parameter has been changed and when its process variable has stabilized.

For example, when the flow rate of the dilution water is changed, such as when an operator changes it or when a DCS 94 changes it in response to a change in motor load, the controller 274 is put on hold at the time designated by line 300 (FIG. 21). A link 92
5 between the DCS 94 and the control computer 38 can communicate when such a refiner operating parameter has been changed and thereby cause the controller 274 to be put on hold.

After the operating parameter change has been made, the refiner 32 begins to stabilize. For example, where refiner temperature is the process variable, the
10 temperature will change and then stabilize in the manner shown in FIGS. 22. Where consistency is the process variable, it too will stabilize. When the process variable has sufficiently stabilized, its value when the stabilization determination is made is adopted as the new setpoint and the controller 274 is released, such as at the time indicated by line 302. When released, the controller resumes operation.

15 The control processor 34 preferably is configured with the control method of this invention or a preferred implementation of the control method. The control method preferably is implemented in software on board the control processor 34. Preferably, the control method is implemented in the form of a controller that preferably is a PI controller or a PID controller.

20 It is also to be understood that, although the foregoing description and drawings describe and illustrate in detail one or more preferred embodiments of the present

invention, to those skilled in the art to which the present invention relates, the present disclosure will suggest many modifications and constructions as well as widely differing embodiments and applications without thereby departing from the spirit and scope of the invention. The present invention, therefore, is intended not to be limited by the

5 foregoing description.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
221